NSN 5930-00-240-4206

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-240-4206

| Body Style: |
|---|
| Bushing mounted |
| Hazardous Locations/environmental Protection: |
| Dustproof |
| Overall Length: |
| 1.891 inches |
| Body Diameter: |
| 0.562 inches |
| Bushing Length: |
| 0.625 inches |
| Body Length: |
| 0.422 inches |
| Actuator Diameter: |
| 0.312 inches |
| Actuator Height: |
| 0.438 inches |
| Actuator Color: |
| Red single actuator |
| Maximum Voltage Rating In Volts: |
| 120.0 ac |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing |
| Thready Qty Per Inch (tpi): |
| 24 |
| Thread Size: |
| 0.625 inches |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, double make, both positions maintained single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 10.000 amperes resistive ac |
| Thread Series Designator: |
| Unef |
| Terminal Type And Quantity: |
| 2 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5930-00-240-4206

Push Switch - Page 2 of 2



Fiig:

A053a0