## NSN 5930-00-241-1334

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-241-1334

| Thread Class.  |
|--|
| Thread Class:  |
| 2a   |
| Body Style:  |
| Bushing mount  |
| Hazardous Locations/environmental Protection:                      |
| Dustproof and watertight   |
| Bushing Length:  |
| 0.340 inches   |
| Body Length:   |
| 1.880 inches   |
| Body Width:  |
| 1.300 inches   |
| Body Height:   |
| 1.400 inches   |
| Actuator Style:  |
| Rectangular  |
| Actuator Height:   |
| 1.247 inches   |
| Actuator Position-action Relationship:                             |
| Up position maintained and down position maintained                |
| Maximum Voltage Rating In Volts:                                   |
| 250.0 ac and 30.0 dc   |
| End Application:   |
| Aircraft galaxy c-5  |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Method:   |
| Threaded bushing   |
| Features Provided:   |
| Actuator seal  |
| Thready Qty Per Inch (tpi):  |
| 32   |
| Thread Size:   |
| 0.469 inches   |
| Nonpile-up Contact Arrangement:                                    |
| 8 pole, double throw, both positions maintained single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage:              |
| 5.000 amperes resistive dc and 5.000 amperes resistive ac          |
| Thread Series Designator:  |
| Uns  |
| Terminal Type And Quantity:  |

24 wire lead

## NSN 5930-00-241-1334

Toggle Switch - Page 2 of 2



| _ |   |            |   |    |    |
|---|---|------------|---|----|----|
| • | n | <b>0</b> 1 | • | 12 | e: |
|   |   |            |   |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0