

View Online at <https://aerobasegroup.com/nsn/5930-00-241-8955>

**Body Style:**

Hole mounted

**Overall Length:**

Between 1.933 inches and 1.943 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.995 inches and 1.002 inches

**Overall Height:**

Between 0.839 inches and 0.849 inches

**Overall Width:**

Between 0.683 inches and 0.693 inches

**Body Length:**

Between 1.933 inches and 1.943 inches

**Body Width:**

Between 0.683 inches and 0.693 inches

**Body Height:**

Between 0.839 inches and 0.849 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.139 inches and 0.142 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.229 inches and 0.239 inches

**Actuator Adapter Style:**

Pushbutton

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

Between 0.995 inches and 1.005 inches

**Maximum Voltage Rating In Volts:**

460.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

13.0 ounces

**Actuator Movement:**

Between 0.020 pretravel inches and 0.052 overtravel inches and 0.0020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0