

View Online at <https://aerobasegroup.com/nsn/5930-00-241-8955>

Body Style:

Hole mounted

Overall Length:

Between 1.933 inches and 1.943 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.995 inches and 1.002 inches

Overall Height:

Between 0.839 inches and 0.849 inches

Overall Width:

Between 0.683 inches and 0.693 inches

Body Length:

Between 1.933 inches and 1.943 inches

Body Width:

Between 0.683 inches and 0.693 inches

Body Height:

Between 0.839 inches and 0.849 inches

Unthreaded Mounting Hole Diameter:

Between 0.139 inches and 0.142 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.229 inches and 0.239 inches

Actuator Adapter Style:

Pushbutton

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

Between 0.995 inches and 1.005 inches

Maximum Voltage Rating In Volts:

460.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

13.0 ounces

Actuator Movement:

Between 0.020 pretravel inches and 0.052 overtravel inches and 0.0020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0