## NSN 5930-00-242-4919

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-242-4919

Housing Height:
1.406 inches
Housing Width:
1.031 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
1.688 inches
Maximum Voltage Rating In Volts:
250.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Switch Release Force:
8.0 ounces
Switch Actuating Force:
80.0 ounces
Actuator Movement:
Between 0.078 pretravel inches and 0.250 overtravel inches and 0.031 differential inches
Between 0.078 pretravel inches and 0.250 overtravel inches and 0.031 differential inches  Contact Load Current Rating At Maximum Rated Voltage:
Contact Load Current Rating At Maximum Rated Voltage:
Contact Load Current Rating At Maximum Rated Voltage: 6.000 amperes resistive dc and 10.000 amperes resistive ac
Contact Load Current Rating At Maximum Rated Voltage: 6.000 amperes resistive dc and 10.000 amperes resistive ac Terminal Type And Quantity:
Contact Load Current Rating At Maximum Rated Voltage: 6.000 amperes resistive dc and 10.000 amperes resistive ac Terminal Type And Quantity: 6 screw
Contact Load Current Rating At Maximum Rated Voltage: 6.000 amperes resistive dc and 10.000 amperes resistive ac Terminal Type And Quantity: 6 screw Shelf Life:
Contact Load Current Rating At Maximum Rated Voltage:  6.000 amperes resistive dc and 10.000 amperes resistive ac  Terminal Type And Quantity:  6 screw  Shelf Life:  N/a
Contact Load Current Rating At Maximum Rated Voltage:  6.000 amperes resistive dc and 10.000 amperes resistive ac  Terminal Type And Quantity:  6 screw  Shelf Life:  N/a  Unit Of Measure:
Contact Load Current Rating At Maximum Rated Voltage:  6.000 amperes resistive dc and 10.000 amperes resistive ac  Terminal Type And Quantity:  6 screw  Shelf Life:  N/a  Unit Of Measure:
Contact Load Current Rating At Maximum Rated Voltage:  6.000 amperes resistive dc and 10.000 amperes resistive ac  Terminal Type And Quantity:  6 screw  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:
Contact Load Current Rating At Maximum Rated Voltage:  6.000 amperes resistive dc and 10.000 amperes resistive ac  Terminal Type And Quantity:  6 screw  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No
Contact Load Current Rating At Maximum Rated Voltage:  6.000 amperes resistive dc and 10.000 amperes resistive ac  Terminal Type And Quantity:  6 screw  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:
Contact Load Current Rating At Maximum Rated Voltage:  6.000 amperes resistive dc and 10.000 amperes resistive ac  Terminal Type And Quantity:  6 screw  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig: