NSN 5930-00-242-9968

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-242-9968

Body Style:
Hole mounted
Overall Length:
1.940 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Overall Height:
0.997 inches
Overall Width:
0.687 inches
Body Length:
1.940 inches
Body Width:
0.687 inches
Body Height:
0.950 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Style:
Round
Actuator Diameter:
0.094 inches
Actuator Height:
0.035 inches
Actuator Free Position Height:
0.625 inches
Maximum Voltage Rating In Volts:
240.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
6.0 ounces

Between 11.0 ounces and 15.0 ounces Actuator Movement:

Switch Actuating Force:

Between 0.012 pretravel inches and 0.005 overtravel inches and 0.004 differential inches and 0.0004 differential inches

NSN 5930-00-242-9968

Sensitive Switch - Page 2 of 2

Fiig: A053a0



Contact Load Current Rating At Maximum Rated Voltage:
15.000 amperes resistive ac
Terminal Type And Quantity:
3 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No