

View Online at <https://aerobasegroup.com/nsn/5930-00-242-9978>

Body Style:

Bushing/hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Bushing Length:

0.310 inches

Body Length:

1.937 inches

Body Width:

0.687 inches

Body Height:

0.954 inches

Unthreaded Mounting Hole Diameter:

0.140 inches

Actuator Style:

Round

Actuator Diameter:

0.158 inches

Actuator Height:

0.206 inches

Actuator Free Position Height:

1.110 inches

Maximum Voltage Rating In Volts:

600.0 ac and 230.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

Between 20.0 ounces and 28.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.050 overtravel inches and 0.010 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

300.000 milliamperes resistive dc and 100.000 milliamperes inductive dc and 300.000 milliamperes lamp dc and 100.000 milliamperes motor dc and 2.000 amperes resistive ac and 500.000 milliamperes lamp ac and 2.000 amperes motor ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0