NSN 5930-00-242-9979

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-242-9979

Body Style:						
Hole mounted						
Hazardous Locations/environmental Protection:						
Dustproof						
Overall Length:						
1.188 inches						
Center To Center Distance Between Mounting Facilities Parallel To Length:						
1.000 inches						
Overall Height:						
0.891 inches						
Overall Width:						
0.266 inches						
Body Length:						
1.188 inches						
Body Width:						
0.266 inches						
Body Height:						
0.812 inches						
Case Material:						
Plastic						
Unthreaded Mounting Hole Diameter:						
0.094 inches						
Center To Center Distance Between Mounting Facilities Parallel To Height:						
0.625 inches						
Actuator Style:						
Round						
Actuator Height:						
0.172 inches						
Actuator Free Position Height:						
0.797 inches						
Maximum Voltage Rating In Volts:						
230.0 ac						
Inclosure Type:						
Fully enclosed						
Mounting Method:						
Unthreaded hole						
Nonpile-up Contact Arrangement:						
1 pole, double throw, one position momentary single switch unit						
Switch Release Force:						
4.0 ounces						
Switch Actuating Force:						

16.0 ounces

NSN 5930-00-242-9979

Sensitive Switch - Page 2 of 2



Δ	ctu	ator	·Mc	WA	mar	١+.
н	CLU	alui	IVIC	vei	пег	H.

Between 0.031 pretravel inches and 0.025 overtravel inches and 0.015 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0