NSN 5930-00-243-4473



Push Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-243-4473 **Body Style:** Hole mount **Overall Height:** 1.063 inches **Overall Width:** 1.375 inches **Body Diameter:** 1.375 inches **Body Height:** 0.938 inches **Case Material: Plastic Unthreaded Mounting Hole Diameter:** 0.112 inches Center To Center Distance Between Mounting Facilities Parallel To Diameter: 0.750 inches **Switch Actuator Quantity:** 3 **Maximum Voltage Rating In Volts:** 120.0 ac and 120.0 dc **End Application:** Ticonderoga class cg (47), sturgeon class ssn (637), austin ship class lpd-4 amphibious transport docks, nimitz class cvn, emory s. Land class as, spruance class dd (963) **Inclosure Type:** Fully enclosed **Mounting Method:** Unthreaded hole **Nonpile-up Contact Arrangement:** 3 pole, single throw, normally open, double make, momentary action single switch unit **Criticality Code Justification:** Feat **Contact Load Current Rating At Maximum Rated Voltage:** 5.000 amperes resistive dc and 5.000 amperes resistive ac **Special Features:** Weapon system essential **Terminal Type And Quantity:** 6 pin Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 5930-00-243-4473Push Switch - Page 2 of 2



Fiig:

A053a0