# NSN 5930-00-243-4473

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-243-4473

## Body Style:

Hole mount

**Overall Height:** 

1.063 inches

# Overall Width:

1.375 inches

# Body Diameter:

1.375 inches

## **Body Height:**

0.938 inches

# Case Material:

Plastic

# Unthreaded Mounting Hole Diameter:

# 0.112 inches

# Center To Center Distance Between Mounting Facilities Parallel To Diameter:

# 0.750 inches

# Switch Actuator Quantity:

3

#### Maximum Voltage Rating In Volts:

120.0 ac and 120.0 dc

#### End Application:

Ticonderoga class cg (47), sturgeon class ssn (637), austin ship class lpd-4 amphibious transport docks, nimitz class cvn, emory s. Land class as, spruance class dd (963)

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Unthreaded hole

#### Nonpile-up Contact Arrangement:

3 pole, single throw, normally open, double make, momentary action single switch unit

#### Criticality Code Justification:

Feat

#### Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 5.000 amperes resistive ac

#### **Special Features:**

Weapon system essential

# Terminal Type And Quantity:

6 pin

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

# **NSN 5930-00-243-4473** Push Switch - Page 2 of 2

Fiig: A053a0

