# NSN 5930-00-243-5884

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-243-5884

# **Thread Class:**

2a single mounting facility

#### Thread Length:

0.250 inches single mounting facility

# **Overall Length:**

2.019 inches

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.813 inches single actuator

#### **Overall Diameter:**

1.250 inches

Individual Section Quantity:

1

#### **Operating Tempurature Range:**

-65.0/+85.0 degrees celsius

### Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

1 single section rear

# Throw Quantity:

2 single section rear

#### Mounting Method:

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

28.0 dc at sea level

#### Switch Actuator Indexing Position Quantity:

2 single actuator

#### Shaft Type:

Round single actuator

# Terminal Type:

Printed circuit

### **Contact Switching Action:**

Breaks before makes single section rear

#### Switch Actuator Positioning Increment:

30.0 degrees single actuator

#### **Detent Rotational Torque Range:**

+10.000/+18.000 inch-ounces single actuator

# Switch Actuator Stop Device Type:

Fixed stop single actuator

# NSN 5930-00-243-5884

Rotary Switch - Page 2 of 2



**Contact Load Current Rating:** 

1.0 amperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0