NSN 5930-00-243-6725

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-243-6725 **Thread Class:** 2b **Body Style:** Hole mounted **Overall Length:** 2.052 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.812 inches **Overall Height:** 1.890 inches **Overall Width:** 0.810 inches **Body Length:** 1.940 inches **Body Width:** 0.690 inches **Body Height:** 0.960 inches **Case Material: Plastic Actuator Style:** Round **Actuator Diameter:** 0.500 inches **Actuator Height:** 0.780 inches **Actuator Free Position Height:** 0.780 inches **Actuator Adapter Style:** Pushbutton Center To Center Distance Between Adapter Mounting Facilities Parallel To Length: 1.812 inches **Maximum Voltage Rating In Volts:** 460.0 ac and 250.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded hole

0.138 inches

Thread Size:

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

NSN 5930-00-243-6725

Sensitive Switch - Page 2 of 2



Switch Actuating Force:
16.0 ounces
Actuator Movement:
Between 0.188 pretravel inches $$ and 0.094 overtravel inches and 0.005 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
250.000 milliamperes resistive dc and 15.000 amperes resistive ac
Thread Series Designator:
Unf
Terminal Type And Quantity:
3 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A053a0