# NSN 5930-00-243-8774

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-243-8774

## Thread Class:

2a single mounting facility

## Thread Length:

0.250 inches single mounting facility

## Hazardous Locations/environmental Protection:

Dustproof

## **Overall Length:**

4.285 inches

## Shaft Diameter:

0.250 inches 1st actuator

## Shaft Length:

1.312 inches 2nd actuator

## **Overall Diameter:**

2.000 inches

## Individual Section Quantity:

4

#### Switch Contact Basic Design:

Nonpile-up nonsymmetrical

#### **Mounting Method:**

Threaded bushing single mounting facility

#### Thread Size:

0.375 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

28.0 dc at sea level

## Switch Actuator Indexing Position Quantity:

7 1st actuator

#### Shaft Type:

Round, hollowed 1st actuator

#### **Terminal Type:**

Tab, solder lug

#### Switch Actuator Positioning Increment:

45.0 degrees 2nd actuator

#### Switch Actuator Stop Device Type:

Fixed stop all actuators

#### **Contact Load Current Rating:**

500.0 milliamperes resistive load ac at sea level

#### Precious Material And Location:

Contct surfaces silver

#### **Precious Material:**

Silver

#### Style Designator:

Circular wafer, bushing mount

# NSN 5930-00-243-8774

Rotary Switch - Page 2 of 2



Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0

