Code Indicating Wheel Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-243-9272

Haz	ardous Locations/environmental Protection:
	tproof
	erall Length:
	20 inches
Ονε	erall Height:
	35 inches
	erall Width:
	20 inches
Unt	hreaded Mounting Hole Diameter:
	40 inches single mounting facility
	vidual Section Quantity:
4	
Lon	gest Horizontal Distance Between Mounting Centers:
	45 inches single mounting facility
	egest Vertical Distance Between Mounting Centers:
	00 inches single mounting facility
	unting Method:
	hreaded hole single mounting facility
	uator Type:
	mbwheel all actuators
Fea	tures Provided:
Rfi s	shielding
Cor	ntact Voltage Rating In Volts:
28.0	) dc at sea level
Μοι	unting Facility Pattern:
Fou	r position rectangular single mounting facility
Swi	tch Actuator Indexing Position Quantity:
10 a	all actuators
Terr	minal Type:
Prin	ted circuit
Cor	ntact Load Current Rating:
125	.0 milliamperes resistive load dc at sea level
Rea	idout Indicator Marking:
0, 1	, 2, 3, 4, 5, 6, 7, 8, 9 each section
Cor	ntact Arrangement Truth Table:
Bcd	, 1 pole - 10 positions each section
Col	or:
Whi	te each indicator marking
Pre	cious Material And Location:
Con	tacts silver and circuit plating gold
Pre	cious Material:
Silv	er and gold



Style Designator:

Rectangular inline indicating

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

Fiig:

A052b0