## NSN 5930-00-243-9302

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-243-9302 **Thread Class:** 2b **Body Style:** Hole mount **Hazardous Locations/environmental Protection:** Vibration resistant **Overall Length:** 2.000 inches **Center To Center Distance Between Mounting Facilities Parallel To Length:** 1.500 inches **Overall Height:** 2.775 inches **Overall Width:** 1.720 inches **Body Length:** 2.000 inches **Body Width:** 1.680 inches **Body Height:** 1.380 inches **Actuator Style:** Round **Actuator Diameter:** 0.290 inches **Actuator Height:** 1.195 inches **Actuator Position-action Relationship:** Up position maintained and down position maintained and center position maintained **Actuator Position-locking Relationship:** Up position no locking action and down position no locking action and center position locked in **Maximum Voltage Rating In Volts:** 28.0 dc **End Application:** F-111 aircraft, f-111 simulator. **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded hole

**Features Provided:** 

Holding solenoid

Thready Qty Per Inch (tpi):

32

## **NSN 5930-00-243-9302** Toggle Switch - Page 2 of 2

Thread Size:



0.138 inches
Nonpile-up Contact Arrangement:
4 pole, double throw, three positions maintained single switch unit
Criticality Code Justification:
Feat
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 2.500 amperes inductive dc
Special Features:
Flight safety critical
Thread Series Designator:
Unc
Terminal Type And Quantity:
14 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A053a0