NSN 5930-00-244-5006

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-244-5006

Overall Length:
1.952 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 0.998 inches and 1.002 inches
Overall Height:
0.875 inches
Overall Width:
0.703 inches
Body Length:
1.952 inches
Body Width:
0.703 inches
Body Height:
0.828 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
Between 0.139 inches and 0.143 inches
Actuator Length:
0.047 inches
Actuator Style:
Round
Actuator Diameter:
0.375 inches
Actuator Height:
0.047 inches
Actuator Free Position Height:
0.047 inches
Maximum Voltage Rating In Volts:
24.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, single throw, both positions maintained single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:

Actuator Movement:

Between 14.0 ounces and 20.0 ounces

Between 0.020 pretravel inches and 0.050 overtravel inches and 0.001 differential inches and 0.003 differential inches

NSN 5930-00-244-5006 Sensitive Switch - Page 2 of 2

Fiig: A053a0



Contact Load Current Rating At Maximum Rated Voltage:	
10.000 amperes resistive dc	
Terminal Type And Quantity:	
2 screw	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	