## NSN 5930-00-244-8959

Thermostatic Switch - Page 1 of 2

Disc w/flange



View Online at https://aerobasegroup.com/nsn/5930-00-244-8959

Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
1.125 inches
Overall Height:
0.603 inches
Body Diameter:
0.660 inches
Body Height:
0.305 inches
Unthreaded Mounting Hole Diameter:
0.147 inches
Distance Between Mounting Facility Centers:
0.875 inches
Tempurature Sensing Element Type:
Internal sensor
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
5.0 amperes resistive load single voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
77.00 actuation point degrees fahrenheit and 57.00 deactuation point degrees fahrenheit
Contact Voltage Rating In Volts:
125.0 ac at sea level single voltage
Frequency In Hertz:
60.0 single voltage
Media For Which Designed:
Gas or liquid
Style Designator:

## NSN 5930-00-244-8959

Thermostatic Switch - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0