

View Online at <https://aerobasegroup.com/nsn/5930-00-244-8959>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

1.125 inches

Overall Height:

0.603 inches

Body Diameter:

0.660 inches

Body Height:

0.305 inches

Unthreaded Mounting Hole Diameter:

0.147 inches

Distance Between Mounting Facility Centers:

0.875 inches

Temperature Sensing Element Type:

Internal sensor

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

77.00 actuation point degrees fahrenheit and 57.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

125.0 ac at sea level single voltage

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Disc w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0