

View Online at <https://aerobasegroup.com/nsn/5930-00-246-8827>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

1.423 inches

Overall Height:

0.330 inches

Body Diameter:

0.650 inches

Mounting Slot Width:

0.104 inches

Body Height:

0.325 inches

Distance Between Mounting Facility Centers:

0.968 inches

Temperature Sensing Element Type:

Internal sensor

Mounting Method:

Bracket and slot

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

2.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

143.00 actuation point degrees fahrenheit and 152.00 actuation point degrees fahrenheit and 2.00 differential point degrees fahrenheit and 5.00 differential point degrees fahrenheit

Contact Voltage Rating In Volts:

30.0 dc at sea level second voltage

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas

Unpackaged Unit Weight:

7.000 grams

Style Designator:

Disc w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0