NSN 5930-00-246-9370

Lever Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-246-9370 **Thread Class:** 2a **Body Style: Bushing mounted Overall Length:** 1.204 inches **Overall Height:** 3.688 inches **Overall Width:** 0.625 inches **Bushing Length:** 0.313 inches **Body Width:** 0.625 inches **Body Height:** 1.204 inches **Actuator Style:** Round **Actuator Height:** 0.937 inches **Actuator Position-action Relationship:** Center position maintained and left position maintained and right position maintained **Actuator Position-locking Relationship:** Center position no locking action and left position no locking action and right position locked in **Actuator Color:** Black single actuator **Maximum Voltage Rating In Volts:** 115.0 ac **Inclosure Type:** Uninclosed **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi): 32 **Pile-up Contact Form Arrangement:** 4a 2nd position **Thread Size:** 0.469 inches

3.000 amperes resistive ac

Precious Material And Location:

Springs silver and contacts palladium

Contact Load Current Rating At Maximum Rated Voltage:

NSN 5930-00-246-9370

Lever Switch - Page 2 of 2



Thread Series Designator:
Uns
Terminal Type And Quantity:
10 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0