# NSN 5930-00-247-9279

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-247-9279

# Thread Class:

2a single mounting facility

### Thread Length:

0.468 inches single mounting facility

## Hazardous Locations/environmental Protection:

Explosion proof

#### **Overall Length:**

4.207 inches

#### **Overall Diameter:**

2.000 inches

Individual Section Quantity:

3

Knob Manufacturer Code:

82121

#### Nonturn Device Type:

Slotted bushing at 12: 00 o'clock

#### Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

2 each section front

## Throw Quantity:

2 each section front

#### **Mounting Method:**

Threaded bushing single mounting facility

#### **Features Provided:**

Actuator knob

#### Thready Qty Per Inch (tpi):

32 single mounting facility

#### Thread Size:

0.469 inches single mounting facility

#### Contact Voltage Rating In Volts:

30.0 dc at sea level

#### **Switch Actuator Momentary Position:**

Clockwise single actuator

#### Switch Actuator Indexing Position Quantity:

2 single actuator

**Terminal Type:** 

Tab w/screw

#### **Contact Switching Action:**

Breaks before makes each section front

## Switch Actuator Positioning Increment:

45.0 degrees single actuator

# NSN 5930-00-247-9279

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 5.0 amperes resistive load dc at sea level Style Designator: Tap, circular, bushing mount **Thread Series Designator:** Uns single mounting facility Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A052b0