

View Online at <https://aerobasegroup.com/nsn/5930-00-248-0983>

Hazardous Locations/environmental Protection:

Moisture proof

Overall Length:

4.938 inches

Body Diameter:

Between 0.618 inches and 0.625 inches

Body Length:

3.594 inches

Overall Diameter:

1.750 inches

Unthreaded Mounting Hole Diameter:

Between 0.169 inches and 0.171 inches

Longest Horizontal Distance Between Mounting Centers:

Between 1.072 inches and 1.092 inches

Shortest Horizontal Distance Between Mounting Centers:

Between 0.536 inches and 0.546 inches

Temperature Sensing Element Type:

Internal sensor

Operating Temperature Rating:

Between -273.1 degrees celsius and 100.0 degrees fahrenheit

Mounting Method:

Flange and unthreaded hole

Features Provided:

Tamper proof cap

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Wire lead

Contact Load Current Rating:

5.0 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+100.00/+600.00 actuation point degrees fahrenheit and +100.00/+600.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Stimulus Rating:

450.00 actuation point degrees fahrenheit and 440.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level third voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A048b0