

View Online at <https://aerobasegroup.com/nsn/5930-00-248-3427>

Thread Length:

0.375 inches single mounting facility

Overall Length:

4.374 inches

Overall Height:

1.875 inches

Overall Width:

1.625 inches

First Flat Length:

0.625 inches single actuator

Flat Height:

0.217 inches single actuator and 0.219 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

3.062 inches single actuator

Nonturn Device Radius:

0.531 inches at 7: 00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 7: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section rear

Throw Quantity:

4 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

250.0 highest dc voltage rating at sea level

Shaft Flat/slot Angular Location:

150.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

50.0 milliamperes resistive load lowest dc voltage rating at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0