## NSN 5930-00-248-5053

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-248-5053

**Thread Class:** 

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

First Flat Length:

0.344 inches single actuator

Flat Height:

0.219 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.875 inches single actuator

**Individual Section Quantity:** 

1

**Knob Manufacturer Code:** 

44655

**Knob Manufacturer Part Number:** 

4516

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

1 single section rear

**Throw Quantity:** 

5 single section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Features Provided:** 

Actuator knob

Thread Size:

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

600.0 ac at sea level

**Switch Actuator Indexing Position Quantity:** 

5 single actuator

**Shaft Type:** 

Round, flatted single actuator

**Terminal Type:** 

Tab, solder lug

**Contact Switching Action:** 

Breaks before makes single section rear

**Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

## NSN 5930-00-248-5053

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

10.0 amperes resistive load ac at sea level

**Style Designator:** 

Tap, circular, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0