NSN 5930-00-248-5053

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-248-5053

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

First Flat Length:

0.344 inches single actuator

Flat Height:

0.219 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.875 inches single actuator

Individual Section Quantity:

1

Knob Manufacturer Code:

44655

Knob Manufacturer Part Number:

4516

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

5 single section rear

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Actuator knob

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

600.0 ac at sea level

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

NSN 5930-00-248-5053

Rotary Switch - Page 2 of 2



Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0