NSN 5930-00-248-5512

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-248-5512

Thread Class: 2a single mounting facility Thread Length: 0.375 inches single mounting facility **Overall Length:** 2.250 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 1.812 inches single actuator **Overall Diameter:** 1.875 inches **Nonturn Device Radius:** 0.375 inches at 9: 00 o'clock **Individual Section Quantity: Knob Manufacturer Code:** 71590 **Knob Manufacturer Part Number:** 1403 **Nonturn Device Type:** Tab at 9: 00 o'clock **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 single section rear **Throw Quantity:** 11 single section rear **Mounting Method:** Threaded bushing single mounting facility **Features Provided:** Actuator knob **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 11 single actuator **Shaft Type:** Round single actuator **Terminal Type:**

Tab, solder lug

NSN 5930-00-248-5512

Rotary Switch - Page 2 of 2



Contact Switching Action:
Breaks before makes single section rear
Switch Actuator Positioning Increment:
30.0 degrees single actuator
Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
350.0 milliamperes resistive load ac at sea level
Precious Material And Location:
Contacts silver
Precious Material:
Silver
Style Designator:
Circular wafer, bushing mount
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A052b0