NSN 5930-00-248-6339

Rotary Switch - Page 1 of 2



| view Online at https://aerobasegroup.com/hsn/5930-00-246-6339 |
|---|
| Thread Length: |
| 0.250 inches single mounting facility |
| First Flat Length: |
| 0.312 inches single actuator |
| Flat Height: |
| 0.219 inches single actuator |
| Shaft Diameter: |
| 0.250 inches single actuator |
| Shaft Length: |
| 0.625 inches single actuator |
| Individual Section Quantity: |
| 2 |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Pole Quantity: |
| 1 1st section front |
| Throw Quantity: |
| 3 1st section front |
| Mounting Method: |
| Threaded bushing single mounting facility |
| Thread Size: |
| 0.375 inches single mounting facility |
| Switch Actuator Indexing Position Quantity: |
| 3 single actuator |
| Shaft Type: |
| Round, flatted single actuator |
| Terminal Type: |
| Tab, solder lug |
| Contact Switching Action: |
| Breaks before makes 1st section front |
| Switch Actuator Positioning Increment: |
| 60.0 degrees single actuator |
| Special Features: |
| Two dummy terminals on the front of section one and five dummy terminals on the rear of section two |
| Thread Series Designator: |
| Unef single mounting facility |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5930-00-248-6339 Rotary Switch - Page 2 of 2



Fiig:

A052b0