NSN 5930-00-248-9057

Thermostatic Switch - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5930-00-248-9057 |
|---|
| Hazardous Locations/environmental Protection: |
| Vibration resistant |
| Overall Length: |
| 4.562 inches |
| Overall Height: |
| 1.438 inches |
| Overall Width: |
| 1.578 inches |
| Body Length: |
| 3.562 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.221 inches |
| Tempurature Sensing Element Type: |
| Expanding shell |
| Mounting Facility Circle Radius: |
| 0.625 inches |
| Operating Tempurature Rating: |
| Between -273.1 degrees celsius and 1500.0 degrees fahrenheit |
| Mounting Method: |
| Flange and unthreaded hole |
| Contact Action Stimulus: |
| Increase |
| Mounting Facility Pattern: |
| Three position circular |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally open, momentary action |
| Terminal Type: |

Tab w/screw

Contact Load Current Rating:

500.0 milliamperes resistive load third voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

-100.00/+650.00 actuation point degrees fahrenheit

Contact Adjustment Type:

External actuation point screw

Contact Stimulus Rating:

42.00 actuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Media For Which Designed:

Gas or liquid

NSN 5930-00-248-9057

Thermostatic Switch - Page 2 of 2



| Style Designator: |
|-------------------|
| Rectangular |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A048b0