# NSN 5930-00-249-2927

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-249-2927

# **Thread Class:**

2a single mounting facility

# Thread Length:

0.375 inches single mounting facility

# **Overall Length:**

3.687 inches

### **Overall Height:**

1.875 inches

### **Overall Width:**

1.718 inches

### Shaft Diameter:

0.250 inches single actuator

### Shaft Length:

1.875 inches single actuator

### **Nonturn Device Radius:**

# 0.531 inches at 9:00 o'clock

# Individual Section Quantity:

2

### Nonturn Device Type:

Tab at 9: 00 o'clock

# Switch Contact Basic Design:

Nonpile-up symmetrical

# Pole Quantity:

1 each section rear

#### **Throw Quantity:**

11 each section rear

# **Mounting Method:**

Threaded bushing single mounting facility

# **Thread Size:**

0.375 inches single mounting facility

# Contact Voltage Rating In Volts:

28.0 dc at sea level

# Switch Actuator Indexing Position Quantity:

12 single actuator

# Shaft Type:

Round single actuator

# **Terminal Type:**

Clip

#### **Contact Switching Action:**

Breaks before makes each section rear

# Switch Actuator Positioning Increment:

30.0 degrees single actuator

# NSN 5930-00-249-2927

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type: Adjustable stop single actuator **Contact Load Current Rating:** 350.0 milliamperes resistive load ac at sea level **Precious Material And Location:** Clips and rotor surfaces silver **Precious Material:** Silver Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A052b0