

View Online at <https://aerobasegroup.com/nsn/5930-00-249-4587>

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

7.500 inches

Overall Height:

5.750 inches

Overall Width:

2.875 inches

Capillary Tube Length:

420.000 inches

Bulb Length:

6.000 inches

Bulb Diameter:

1.125 inches

Longest Horizontal Distance Between Mounting Centers:

6.625 inches

Longest Vertical Distance Between Mounting Centers:

2.219 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Mounting Method:

Bracket

Contact Action Stimulus:

Increase

Nonpile-up Contact Arrangement:

1 pole, single throw, both positions maintained

Terminal Type:

Tab w/screw

Contact Load Current Rating:

4.6 amperes resistive load fourth voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+60.00/+120.00 actuation point degrees fahrenheit

Contact Adjustment Type:

Internal actuation point screw

Contact Voltage Rating In Volts:

550.0 dc at sea level third voltage

Frequency In Hertz:

60.0 single voltage

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0