## NSN 5930-00-249-7430

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-249-7430

**Thread Class:** 2a single mounting facility **Thread Length:** 0.375 inches single mounting facility **Overall Length:** 2.125 inches **Overall Height:** 2.000 inches **Overall Width:** 1.562 inches **Shaft Diameter:** 0.250 inches single actuator Shaft Length: 0.750 inches single actuator **Individual Section Quantity: Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 4 each section rear **Throw Quantity:** 2 each section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 6.0 lowest dc voltage rating at sea level **Switch Actuator Indexing Position Quantity:** 2 single actuator **Shaft Type:** Round single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Breaks before makes each section rear **Switch Actuator Positioning Increment:** 30.0 degrees single actuator **Switch Actuator Stop Device Type:** Adjustable stop single actuator

**Contact Load Current Rating:** 

5.5 amperes resistive load highest dc voltage rating at sea level

## NSN 5930-00-249-7430

Rotary Switch - Page 2 of 2



Sty	ما	D	20	in	n	2	ŧ۸	r	
JLY	ı	יש	င၁	ıу	••	а	ιυ	ш	

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0