

View Online at <https://aerobasegroup.com/nsn/5930-00-249-8617>

**Body Style:**

Hole mounted

**Overall Length:**

1.187 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.875 inches

**Overall Height:**

0.719 inches

**Overall Width:**

0.400 inches

**Body Length:**

1.093 inches

**Body Width:**

0.400 inches

**Body Height:**

0.625 inches

**Unthreaded Mounting Hole Diameter:**

0.126 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.406 inches

**Actuator Length:**

0.110 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.094 inches

**Actuator Width:**

0.165 inches

**Actuator Free Position Height:**

0.610 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 250.0 dc

**End Application:**

Los angeles class ss (688), sturgeon class(637)trident electric power conversion equipment, seawolf class ssn, trident electric plant, deep submergence systems programs(dssp)

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

4.0 ounces

**Criticality Code Justification:**

Feat

**Switch Actuating Force:**

Between 6.0 ounces and 14.0 ounces

**Actuator Movement:**

Between 0.047 pretravel inches and 0.031 overtravel inches and 0.006 differential inches and 0.016 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 10.000 amperes resistive ac

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0