NSN 5930-00-250-2336

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-250-2336

## **Thread Length:**

0.375 inches single mounting facility

### **Overall Length:**

2.813 inches

# Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.563 inches single actuator

## **Overall Diameter:**

2.000 inches

### Nonturn Device Radius:

0.531 inches at 9:00 o'clock

#### Individual Section Quantity:

1

#### Nonturn Device Type:

Tab at 9: 00 o'clock

#### **Operating Tempurature Range:**

-60.0/+75.0 degrees celsius

## Switch Contact Basic Design:

Nonpile-up symmetrical

### Pole Quantity:

3 single section rear

#### Throw Quantity:

3 single section rear

#### **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

28.0 dc at sea level

#### Switch Actuator Indexing Position Quantity:

3 single actuator

#### Shaft Type:

Round single actuator

#### **Terminal Type:**

Tab, solder lug

#### **Contact Switching Action:**

Breaks before makes single section rear

# Switch Actuator Positioning Increment:

30.0 degrees single actuator

## Switch Actuator Stop Device Type:

Fixed stop single actuator

# NSN 5930-00-250-2336

Rotary Switch - Page 2 of 2



Contact Load Current Rating:

500.0 milliamperes resistive load ac at sea level

### **Precious Material And Location:**

Contacts, rotor blades and terminal surfaces silver

**Precious Material:** 

Silver

Style Designator:

Circular wafer, bushing mount

### **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0