## NSN 5930-00-250-3788

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-250-3788

## Thread Length:

0.375 inches single mounting facility

#### **Hazardous Locations/environmental Protection:**

Fungus resistant and moisture resistant

**Overall Length:** 

1.586 inches

#### First Flat Length:

0.344 inches single actuator

Flat Height:

0.219 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.750 inches single actuator

**Overall Diameter:** 

1.562 inches

## **Individual Section Quantity:**

1

## **Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:** 

3 single section rear

**Throw Quantity:** 

2 single section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Features Provided:** 

Metallic inclosure

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

6.0 dc at sea level

## **Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:** 

Round, flatted single actuator

**Terminal Type:** 

Tab, solder lug

## **Contact Switching Action:**

Breaks before makes single section rear

## **Switch Actuator Positioning Increment:**

60.0 degrees single actuator

# NSN 5930-00-250-3788

Rotary Switch - Page 2 of 2



Contact Load	Current	Rating:
--------------	---------	---------

1.0 amperes resistive load dc at sea level

**Style Designator:** 

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0