# NSN 5930-00-250-3788

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-250-3788

## Thread Length:

0.375 inches single mounting facility

## Hazardous Locations/environmental Protection:

Fungus resistant and moisture resistant

## **Overall Length:**

1.586 inches

## First Flat Length:

0.344 inches single actuator

## Flat Height:

0.219 inches single actuator

## Shaft Diameter:

0.250 inches single actuator

# Shaft Length:

0.750 inches single actuator

# **Overall Diameter:**

1.562 inches

# Individual Section Quantity:

1

## Switch Contact Basic Design:

Nonpile-up symmetrical

## Pole Quantity:

3 single section rear

#### Throw Quantity:

2 single section rear

## **Mounting Method:**

Threaded bushing single mounting facility

## **Features Provided:**

Metallic inclosure

## Thread Size:

0.375 inches single mounting facility

## Contact Voltage Rating In Volts:

6.0 dc at sea level

# Switch Actuator Indexing Position Quantity:

2 single actuator

## Shaft Type:

Round, flatted single actuator

# Terminal Type:

Tab, solder lug

## **Contact Switching Action:**

Breaks before makes single section rear

# Switch Actuator Positioning Increment:

60.0 degrees single actuator

# NSN 5930-00-250-3788

Rotary Switch - Page 2 of 2



**Contact Load Current Rating:** 

1.0 amperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0