## NSN 5930-00-250-5089

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-250-5089

Body Style:
Hole mounted
Overall Length:
1.625 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Overall Height:
0.909 inches
Overall Width:
0.281 inches
Body Length:
1.203 inches
Body Width:
0.281 inches
Body Height:
0.828 inches
Unthreaded Mounting Hole Diameter:
0.094 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.625 inches
Actuator Style:
Round
Actuator Diameter:
0.094 inches
Actuator Height:
0.071 inches
Actuator Free Position Height:
0.172 inches
Maximum Voltage Rating In Volts:
115.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
1.5 ounces
Switch Actuating Force:

Between 3.0 ounces and 6.0 ounces

**Actuator Movement:** 

Between 0.031 pretravel inches and 0.025 overtravel inches and 0.007 differential inches

## NSN 5930-00-250-5089

Sensitive Switch - Page 2 of 2



Contact	I oad (	Current	Rating	At Maximum	Rated	Voltage:

10.000 amperes resistive ac

**Terminal Type And Quantity:** 

3 tab, solder lug

.

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A053a0