

View Online at <https://aerobasegroup.com/nsn/5930-00-250-6482>

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Moisture proof

Overall Length:

3.164 inches

Overall Height:

0.870 inches

Overall Width:

0.870 inches

Body Length:

2.750 inches

Body Width:

0.870 inches

Body Height:

0.870 inches

Case Material:

Metal

Actuator Length:

Between 0.789 inches and 0.851 inches

Actuator Style:

Rectangular

Actuator Height:

Between 0.383 inches and 0.445 inches

Actuator Width:

Between 0.789 inches and 0.851 inches

Actuator Color:

Black single actuator

Illuminated Actuator Color:

White single actuator

Actuator Inscription:

Lru status check single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Aircraft, galaxy c-5

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Rfi shielding and full display lens

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 7.000 amperes resistive ac and 4.000 amperes inductive ac

Special Features:

Weapon system essential

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

3 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0