NSN 5930-00-250-6482

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-250-6482

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Moisture proof
Overall Length:
3.164 inches
Overall Height:
0.870 inches
Overall Width:
0.870 inches
Body Length:
2.750 inches
Body Width:
0.870 inches
Body Height:
0.870 inches
Case Material:
Metal
Actuator Length:
Between 0.789 inches and 0.851 inches
Actuator Style:
Rectangular
Actuator Height:
Between 0.383 inches and 0.445 inches
Actuator Width:
Between 0.789 inches and 0.851 inches
Actuator Color:
Black single actuator
Illuminated Actuator Color:
White single actuator
Actuator Inscription:
Lru status check single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
Aircraft, galaxy c-5
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Rfi shielding and full display lens

NSN 5930-00-250-6482

Push Switch - Page 2 of 2



Nonnile-un	Contact	Arrangement:
Hompile up	Contact	Allangement.

1 pole, double throw, one position momentary single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 7.000 amperes resistive ac and 4.000 amperes inductive ac

Special Features:

Weapon system essential

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

3 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0