

View Online at <https://aerobasegroup.com/nsn/5930-00-250-6482>

**Body Style:**

Panel mounted

**Hazardous Locations/environmental Protection:**

Moisture proof

**Overall Length:**

3.164 inches

**Overall Height:**

0.870 inches

**Overall Width:**

0.870 inches

**Body Length:**

2.750 inches

**Body Width:**

0.870 inches

**Body Height:**

0.870 inches

**Case Material:**

Metal

**Actuator Length:**

Between 0.789 inches and 0.851 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

Between 0.383 inches and 0.445 inches

**Actuator Width:**

Between 0.789 inches and 0.851 inches

**Actuator Color:**

Black single actuator

**Illuminated Actuator Color:**

White single actuator

**Actuator Inscription:**

Lru status check single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

Aircraft, galaxy c-5

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Rfi shielding and full display lens

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Criticality Code Justification:**

Feat

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 7.000 amperes resistive ac and 4.000 amperes inductive ac

**Special Features:**

Weapon system essential

**Precious Material And Location:**

Contacts silver

**Terminal Type And Quantity:**

3 turret and 5 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0