# NSN 5930-00-250-6485

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-250-6485

#### **Body Style:**

Panel mount

#### Hazardous Locations/environmental Protection:

Moisture proof

#### **Overall Length:**

3.164 inches

#### **Overall Height:**

0.870 inches

#### **Overall Width:**

0.870 inches

#### **Body Length:**

2.750 inches

### Body Width:

0.870 inches

## Body Height:

0.870 inches

Case Material:

Metal

#### Actuator Length:

Between 0.789 inches and 0.851 inches

## Actuator Style:

Rectangular

#### Actuator Height:

Between 0.383 inches and 0.445 inches

#### Actuator Width:

Between 0.789 inches and 0.851 inches

#### Actuator Color:

Black single actuator

#### Illuminated Actuator Color:

White single actuator

#### **Actuator Inscription:**

Frame advance single actuator

#### Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Panel

#### **Features Provided:**

Full display lens

#### Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

# NSN 5930-00-250-6485

Push Switch - Page 2 of 2



#### Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 7.000 amperes resistive ac and 4.000 amperes inductive ac

#### **Precious Material And Location:**

Contacts silver

### Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

#### Demilitarization:

No

#### Fiig:

A053a0