

View Online at <https://aerobasegroup.com/nsn/5930-00-250-7991>

**Thread Class:**

2b 2nd mounting facility

**Thread Length:**

0.312 inches 1st mounting facility

**Overall Length:**

3.135 inches

**Overall Height:**

2.062 inches

**Overall Width:**

2.062 inches

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.688 inches single actuator

**Nonturn Device Radius:**

0.500 inches at 12: 00 o'clock

**Individual Section Quantity:**

2

**Nonturn Device Type:**

Tab at 12: 00 o'clock

**Longest Horizontal Distance Between Mounting Centers:**

1.375 inches 2nd mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

2 each section rear

**Throw Quantity:**

2 each section rear

**Mounting Method:**

Threaded hole 2nd mounting facility

**Thready Qty Per Inch (tpi):**

32 2nd mounting facility

**Thread Size:**

0.375 inches 1st mounting facility

**Contact Voltage Rating In Volts:**

30.0 dc at sea level

**Mounting Facility Pattern:**

Two position in-line 2nd mounting facility

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Tab, solder lug and wire lead

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

22.5 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

4.0 amperes resistive load dc at sea level

**Style Designator:**

Square wafer, panel mount

**Thread Series Designator:**

Unef 1st mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0