NSN 5930-00-251-3272

Rotary Switch - Page 1 of 2



30-00-251-3272

View Online at https://aerobasegroup.com/nsn/5930	-
Thread Length:	
0.375 inches single mounting facility	
Hazardous Locations/environmental Protection:	
Dustproof	
Overall Length:	
3.540 inches	
Overall Height:	
2.190 inches	
First Flat Length:	
0.344 inches single actuator	
Flat Height:	
0.219 inches single actuator	
Shaft Diameter:	
0.250 inches single actuator	
Shaft Length:	
0.875 inches single actuator	
Individual Section Quantity:	
2	
Switch Contact Basic Design:	
Nonpile-up symmetrical	
Pole Quantity:	
1 each section rear	
Throw Quantity:	
3 each section rear	
Mounting Method:	
Threaded bushing single mounting facility	
Features Provided:	
Metallic inclosure	
Thread Size:	
0.375 inches single mounting facility	
Contact Voltage Rating In Volts:	
150.0 ac at sea level	
Switch Actuator Indexing Position Quantity:	
3 single actuator	
Shaft Type:	
Round, flatted single actuator	
Terminal Type:	
Tab, solder lug	
Contact Switching Action:	
Breaks before makes each section rear	
Switch Actuator Positioning Increment:	

Switch Actuator Positioning Increment: 30.0 degrees single actuator

NSN 5930-00-251-3272

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

10.0 amperes resistive load ac at sea level

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0