NSN 5930-00-251-3913

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-251-3913

Thread Class: 2a single mounting facility Thread Length: 0.250 inches single mounting facility **Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 1.750 inches **Overall Height:** 1.375 inches **Overall Width:** 1.297 inches First Flat Length: 0.328 inches single actuator Flat Height: 0.216 inches single actuator **Shaft Diameter:** 0.375 inches single actuator **Shaft Length:** 0.375 inches single actuator **Individual Section Quantity:** 1 **Longest Horizontal Distance Between Mounting Centers:** 1.047 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 single section front **Mounting Method:** Threaded bushing single mounting facility **Features Provided:** Metallic inclosure Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.375 inches 1st mounting facility **Mounting Facility Pattern:** Two position in-line single mounting facility **Shaft Type:** Round, flatted single actuator

Terminal Type:

Tab, solder lug

NSN 5930-00-251-3913

Rotary Switch - Page 2 of 2



Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A052b0