# NSN 5930-00-251-7617

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-251-7617

# **Body Style:**

Hole mounted

#### **Overall Length:**

1.625 inches

# Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

#### **Overall Height:**

0.895 inches

#### **Overall Width:**

0.283 inches

#### **Body Length:**

1.200 inches

#### Body Width:

0.283 inches

#### **Body Height:**

0.820 inches

# **Unthreaded Mounting Hole Diameter:**

0.094 inches

## Center To Center Distance Between Mounting Facilities Parallel To Height:

0.625 inches

#### **Actuator Style:**

Round

#### **Actuator Diameter:**

0.093 inches

#### Actuator Height:

0.075 inches

#### **Actuator Free Position Height:**

0.172 inches

## Maximum Voltage Rating In Volts:

250.0 ac

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Unthreaded hole

#### Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

#### Switch Release Force:

2.0 ounces

### Switch Actuating Force:

6.0 ounces

#### **Actuator Movement:**

Between 0.005 pretravel inches and 0.037 overtravel inches and 0.044 overtravel inches and 0.006 differential inches and 0.010 differential

inches

NSN 5930-00-251-7617

Sensitive Switch - Page 2 of 2



# Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive ac

# **Precious Material And Location:**

Contacts gold

# Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

## Fiig:

A053a0