

View Online at <https://aerobasegroup.com/nsn/5930-00-251-9295>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.250 inches single mounting facility

**Width Between Flats:**

0.188 inches single actuator

**Overall Length:**

1.657 inches

**First Flat Length:**

0.265 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.469 inches single actuator

**Overall Diameter:**

2.188 inches

**Nonturn Device Radius:**

0.531 inches at 2: 30 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Tab at 2: 30 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical and nonpile-up nonsymmetrical

**Pole Quantity:**

2 single section rear

**Throw Quantity:**

3 single section rear

**Mounting Method:**

Threaded bushing w/panel seal single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Round, parallel flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

60.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop-breakoff tab single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load dc at sea level

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0