# NSN 5930-00-252-1558

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-252-1558

# Thread Class:

2a single mounting facility

## Thread Length:

0.312 inches single mounting facility

## Hazardous Locations/environmental Protection:

Dustproof

## **Overall Length:**

1.647 inches

## First Flat Length:

0.250 inches single actuator

## Flat Height:

0.094 inches single actuator

## Shaft Diameter:

0.125 inches single actuator

## Shaft Length:

0.375 inches single actuator

**Overall Diameter:** 

0.750 inches

## Nonturn Device Radius:

0.260 inches at 3: 00 o'clock

## Individual Section Quantity:

1

## Nonturn Device Type:

Tab at 3: 00 o'clock

## **Operating Tempurature Range:**

-65.0/+85.0 degrees celsius

## Switch Contact Basic Design:

Nonpile-up symmetrical

## **Pole Quantity:**

4 single section front

## **Throw Quantity:**

3 single section rear

## **Mounting Method:**

Threaded bushing single mounting facility

## Thread Size:

0.250 inches single mounting facility

## **Contact Voltage Rating In Volts:**

28.0 dc at sea level

## Shaft Flat/slot Angular Location:

195.0 degrees from nonturn device single actuator

## **Rotor Through Connection Quantity:**

4 single section

# NSN 5930-00-252-1558

Rotary Switch - Page 2 of 2



# Switch Actuator Indexing Position Quantity:

3 single actuator

## Shaft Type:

Round, flatted single actuator

## **Terminal Type:**

Tab, solder lug

# **Contact Switching Action:**

Breaks before makes single section rear

# Switch Actuator Positioning Increment:

30.0 degrees single actuator

# Detent Rotational Torque Range:

+8.000/+64.000 inch-ounces single actuator

# Switch Actuator Stop Device Type:

Fixed stop single actuator

# **Contact Load Current Rating:**

250.0 milliamperes resistive load dc at sea level and 20.0 milliamperes inductive load dc at sea level

# Precious Material And Location:

Contacts and terminal surfaces gold and terminal surfaces and contacts silver

## **Precious Material:**

Gold and silver

Style Designator:

Tap, circular, bushing mount

# **Thread Series Designator:**

Unef single mounting facility

# Shelf Life:

N/a

# Unit Of Measure:

---

## Demilitarization:

No

## Fiig:

A052b0