NSN 5930-00-252-7044

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-252-7044

Body Style:

Bushing/hole mounted

Overall Length:

1.938 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Overall Height:

1.949 inches

Overall Width:

0.688 inches

Bushing Length:

0.520 inches

Body Length:

1.938 inches

Body Width:

0.688 inches

Body Height:

0.930 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.140 inches

Actuator Style:

Round

Actuator Diameter:

0.220 inches

Actuator Height:

0.339 inches

Actuator Free Position Height:

0.859 inches

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

NSN 5930-00-252-7044

Sensitive Switch - Page 2 of 2



Switch Actuating Force: Between 3.0 ounces and 13.0 ounces Contact Load Current Rating At Maximum Rated Voltage: 250.000 milliamperes resistive dc and 15.000 amperes resistive ac Thread Series Designator: Uns Terminal Type And Quantity: 3 screw

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0