NSN 5930-00-252-7049

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-252-7049
Body Style:
Hole mounted
Overall Length:
2.461 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Overall Height:
1.658 inches
Overall Width:
0.688 inches
Body Length:
1.925 inches
Body Width:
0.688 inches
Body Height:
0.938 inches
Unthreaded Mounting Hole Diameter:
0.1405 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
1.313 inches
Actuator Roller Diameter:
0.375 inches
Actuator Roller Width:
0.187 inches

Maximum Voltage Rating In Volts:

460.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

0.5 ounces

Switch Actuating Force:

6.0 ounces

Actuator Movement:

0.188 pretravel inches and 0.062 overtravel inches and 0.050 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 5.000 amperes inductive dc and 5.000 amperes motor dc and 15.000 amperes resistive ac

NSN 5930-00-252-7049

Sensitive Switch - Page 2 of 2



Special Features:
Contact gap 0.040
Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
3 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0