

View Online at <https://aerobasegroup.com/nsn/5930-00-252-7049>

Body Style:

Hole mounted

Overall Length:

2.461 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Overall Height:

1.658 inches

Overall Width:

0.688 inches

Body Length:

1.925 inches

Body Width:

0.688 inches

Body Height:

0.938 inches

Unthreaded Mounting Hole Diameter:

0.1405 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

1.313 inches

Actuator Roller Diameter:

0.375 inches

Actuator Roller Width:

0.187 inches

Maximum Voltage Rating In Volts:

460.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

0.5 ounces

Switch Actuating Force:

6.0 ounces

Actuator Movement:

0.188 pretravel inches and 0.062 overtravel inches and 0.050 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 5.000 amperes inductive dc and 5.000 amperes motor dc and 15.000 amperes resistive ac

Special Features:

Contact gap 0.040

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0