NSN 5930-00-252-8784

Lever Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-252-8784 **Thread Class:** 2b **Body Style:** Hole mounted **Overall Length:** Between 3.827 inches and 3.921 inches **Overall Height:** 1.156 inches **Overall Width:** Between 1.015 inches and 1.047 inches **Body Length:** Between 3.781 inches and 3.843 inches **Body Width:** Between 1.015 inches and 1.047 inches **Body Height:** Between 0.702 inches and 0.725 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.807 inches and 0.817 inches **Actuator Style:** Round **Actuator Height:** Between 1.046 inches and 1.078 inches **Actuator Position-action Relationship:** Up position momentary and down position momentary and center position momentary **Actuator Color:** Red single actuator **Maximum Voltage Rating In Volts:** 28.0 dc **Inclosure Type:** Uninclosed **Mounting Method:** Threaded hole Thready Qty Per Inch (tpi): 56 **Pile-up Contact Form Arrangement:** 3c2d 2nd position **Thread Size:** 0.086 inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc

Thread Series Designator:

Unc

NSN 5930-00-252-8784

Lever Switch - Page 2 of 2



Terminal Type A	and Quantity	/ :
-----------------	--------------	------------

24 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0